

CLAIMS

1. A kind of electric machinery by using centrifugal force to produce rotor axial activation modulation is between the rotating shaft of the electric machinery and the electric machinery rotor or between the electric machinery rotor and the stator, or between the rotating shaft of the electric machinery and the stator, there is installed an axial activation mechanism by using centrifugal force and there is installed an axial pre-stressed spring, and to the rotating shaft of the electric machinery there can be selectively installed an axial position limitation structure, and by making use of the speed of the electric machinery rotor, to modulate the electric machinery rotor to produce corresponding axial displacement, and further to modulate the characteristics of the electric machinery between the electric machinery rotor and the electric machinery magnetic field. Its main constituents include:
 - Electric machinery magnetic field F100: Including the constituents of DC or AC generators or motors structures; These structures include:
 - F1: Between the poles of the electric machinery magnetic field and the electric machinery rotor of which the electric machinery magnetic field exhibits normal stable even distribution; or
 - F2: Between the poles of the electric machinery magnetic field and the electric machinery rotor of which the axial single side or double sides exhibit different electric machinery magnetic field intensity; or
 - F3: Between the poles of the electric machinery magnetic field and the electric machinery rotor of which the axial

single side or double sides exhibit different gap structures with electric machinery rotor; or

F4: Between the poles of the electric machinery magnetic field and the electric machinery rotor whose axial single side or double sides consist of multiple permanent magnetic poles or magnetic poles excited by magnetic windings W100 or combinations of both which consist of axial serial structures; or

F5: The structures formed by two or more of the structures described in F1 through F4;

—The electric machinery rotor R100: Including single or mixed electric machinery rotors consist of various commonly used AC or DC generators or motors such as permanent, salient, hysteresis, wound, brush, turbo, squirrel-cage type AC or DC or brush or brushless, synchronous or asynchronous;

—Centrifugal pulling structure FCD100: Including the structures consist of commonly used axial pulling structure due to centrifugal force, and with pre-stressed spring SP100 which exhibit regression during deceleration that will pull the rotor to produce corresponding displacement depending on the speed of the electric machinery rotor, which will alter the relative positions between the electric machinery rotor R100 and electric machinery magnetic field F100, which will produce the relative settings between the electric machinery rotor R100 and the electric machinery magnetic field F100.

2. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, between the shaft of the electric machinery S100 and the

0053375-052704

stator H100 there is installed bearing B100, and between
the electric machinery rotor R100 and the rotating shaft
of the electric machinery S100 there is installed a rotating
transmission and axial displacement structure such as
5 plum-flower shape shaft or any other key way structure for
axial displacement SL100, or further in between the
groove-like linear interactive bodies there is installed
a ball bearing or roller bearing structure, and in between
the electric machinery rotor R100 and the electric machinery
10 shaft S100 there is installed a centrifugal pulling structure
FCD100, in the centrifugal pulling structure FCD100 there
is installed a centrifugal weight FW500, in the centrifugal
weight FW500 there is installed a pivotal joint structure
SC500 for the coupling of movable arms on both sides of movable
15 arms A500, of which one of the movable arm A500 for the
connection to the fixing seat C100 installed with pivotal
joint structure SC500, and the movable arm A500 on the other
side is for the connection to the pivotal joint structure
SC500 for the connection to fixing seat of the electric
20 machinery rotor R100 (or the fixing seat of the body extension
of the electric machinery rotor C300). Between the fixing
seat C100 of the electric machinery rotating shaft S100 and
the electric machinery rotor R100 there is installed an axial
pre-stressed spring SP100 exhibiting regression during
25 deceleration, and to the rotating shaft of the electric
machinery S100 there is installed an optional axial position
limiting structure D100, and when the electric machinery
rotor R100 is functioning as a generator or as a motor, using
the speed of the electric machinery rotor R100 to control
30 the centrifugal pulling structure FCD100 such that the

centrifugal force varies according to the rotor speed, and further to drive the electric machinery rotor to produce axial displacement along the preset direction, so as to generate the corresponding settings of generator or motor characteristics between the electric machinery rotor R100 and the electro-magnetic field F100.

3. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, has a centrifugal pulling structure FCD100 that is installed between the electric machinery rotor R100 and the stator H100 which can manifest regression coupling and has the function of resisting pulling force along axial direction; and between the electric machinery rotor R100 and the rotating shaft of the electric machinery S100, there is installed a plum-flower-shaped shaft or any other similar key way structure SL100 that can produce axial displacement, or further in between the groove-like linear interactive bodies there is installed a linear ball bearing or roller bearing structure, and on one side of the centrifugal pulling structure FCD100 is for the connection to the pivotal joint structure SC500, so as to connect the movable arms A500 on both side, and the movable arm A500 on one side, for connecting to the fixing seat C300 of the electric machinery rotor R100 (or the fixing seat of the body extension of the electric machinery rotor structure) so as to combine with the electric machinery rotor, and the movable arm A500 on the other side for the connection to the circular washer WS100, and the fixing seat C200 coupled through bearing B200 and form regression coupling with the stator H100 and with axial

resisting pulling force function; between the washer WS100 of the centrifugal pulling structure FCD100 and the fixing seat C300 for the connection to the electric machinery rotor R100, there is of this invention of which between the electric machinery rotor and inner wall of the stator there is installed the centrifugal pulling structure for the pulling of the electric machinery rotor to produce axial activation modulation. The cross sectional view along A-A' is the same as Fig. 2. This electrical machinery which can produce axial activation modulation by the use of centrifugal force, has a centrifugal pulling structure FCD100 that is installed between the electric machinery rotor R100 and the stator H100 which can manifest control the speed of the centrifugal pulling structure FCD100 and varies the centrifugal force, and further drives the electric machinery rotor R100 to produce axial displacement in the preset direction, and with the electro-magnetic field F100 to produce corresponding settings of the characteristics of the generator or motor.

4. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, by using the centrifugal pulling structure FCD100, for the installation in between the electric machinery rotor R100 and the stator H100 and exhibiting rotating coupling and has the function of resisting pulling force along axial direction; whereas the electric machinery rotor R100 combined with the rotating shaft of the electric machinery S100, on the side of the centrifugal pulling structure FCD100 for the connection to the pivotal joint structure SC500, to connect the movable arm A500 on both sides, of which the

axial displacement along the preset direction, and to produce electrical generator or electric motor characteristics with the electric machinery magnetic field F100.

5. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, in between the rotating shaft S100 of the electric machinery of the electric machinery rotor R100 and the inner wall of the motor H100 there can be installed a centrifugal pulling mechanism, for the pulling of the rotating shaft of the electric machinery S100 to produce axial displacement, in the centrifugal pulling mechanism FCD100 there is installed the centrifugal weight FW500, in the centrifugal weight FW500 there is installed the pivotal joint structure SC500 for the coupling of movable arm A500, of these one of the movable arm A500 is for connecting to the fixing seat C100 and in turn connected to the rotating shaft S100 of the electric machinery, and the movable arm A500 on the other side is for connecting to the circular washer WS100, and through the bearing B200 coupled to the fixing seat C200 installed with pivotal joint SC500 and connected to the inner wall of the motor H100, and enabling between the centrifugal pulling mechanism FCD100 and the stator H100 to exhibit rotating coupling and with axial resisting force function, between the circular washer WS100 installed on the centrifugal pulling mechanism FCD100 and the fixing seat C100 for the connection to the rotor shaft S100 of the electric machinery, there can be installed a pre-stressed spring exhibiting axial regression during deceleration, between the rotating shaft S100 of the electric machinery and the

stator H100, there is installed the adaptor sleeve or bearing SB100 for the axial displacement and rotating driving for the coupled rotating shaft SB100 of the electric machinery, which can be used for the axial position fixing between the adaptor sleeve for axial displacement and rotating driving and the bearing SB100 and the stator H100, and simply for the rotating shaft S100 of the electric machinery to perform axial displacement rotating driving function, so that when the electric machinery rotor R100 and the rotating shaft of the electric machinery S100 is performing generator function operation or motor function operation, depending on it's speed, with the help of the centrifugal pulling mechanism FCD100 which varies the centrifugal force and the action of the axial pre-stressed spring SP100, so as to drive the rotating shaft of the electric machinery S100 to produce the axial displacement along the preset direction, and further for the axial pulling of the electric machinery rotor R100 to produce the corresponding settings of the characteristics of electrical generator or electrical motor with the electric machinery magnetic field F100.

6. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, in between the rotating shaft S100 of the electric machinery exterior to the motor shell H100 of the rotor of the electric machinery R100 and the motor shell H100 there can be installed a centrifugal pulling mechanism FCD100, for the pulling of the rotating shaft of the electric machinery S100 to produce axial displacement, in the centrifugal pulling mechanism FCD100 there is installed the centrifugal weight FW500, in

the centrifugal weight FW500 there is installed the pivotal joint structure SC500 for the coupling of movable arm A500, of these one of the movable arm A500 is for connecting to the fixing seat C100 and in turn connected to the rotating shaft S100 of the electric machinery, and the movable arm A500 on the other side is for connecting to the circular washer WS100, and through the bearing B200 coupled to the fixing seat C200 installed with pivotal joint SC500 and connected to the inner wall of the motor H100, and enabling between the centrifugal pulling mechanism FCD100 and the stator H100 to exhibit rotating coupling and with axial resisting force function, of which between the circular washer WS100 installed on the centrifugal pulling mechanism FCD100 and the fixing seat C100 for the connection to the rotor shaft S100 of the electric machinery, there can be installed a pre-stressed spring which is exhibiting axial regression during deceleration, between the rotating shaft S100 of the electric machinery and the stator H100, there is installed the adaptor sleeve or bearing SB100 for the axial displacement and rotating driving for the coupled rotating shaft SB100 of the electric machinery, which can be used for the axial position fixing between the adaptor sleeve or the bearing SB100 for the displacement and the rotating driving and the stator H100, and simply for the rotating shaft S100 of the electric machinery to perform axial displacement rotating driving function, so that when the electric machinery rotor R100 and the rotating shaft of the electric machinery S100 is performing the generator function operation or the motor function operation, depending on its speed, with the help of the centrifugal

pulling mechanism FCD100 which varies the centrifugal force and through the action of the axial pre-stressed spring SP100, using the rotating shaft of the electric machinery S100 to produce the axial displacement along the preset direction, and further for the axial pulling of the electric machinery rotor R100 to produce the corresponding settings of the characteristics of generator or motor with the electro-magnetic field F100.

7. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, can be further modified to the structure of an individual electric machinery magnetic field structure F100 coupled to two individual electric machinery rotors and constitute the dual electric machinery rotor structure; The previously described structures between the dual rotors R100' and R100'' and the rotating shaft of the electric machinery can be fixed connection or installed with plum-flower shape shaft, or any other key way structure SL100 which can be used for axial displacement or further in between the groove-like linear interactive bodies there is installed a linear ball bearing or roller bearing structure rotating shaft of electric machinery, including the structure consist of one common electric machinery shaft S100''' or two sections comprising of two separate electric machinery shafts S100' and S100''. The previously described structure of two individual electric machinery rotors for the coupling to one each individual electric machinery magnetic field F100, the two individual electric machinery rotors can have either the same characteristics or different electric machinery rotor

machinery shaft S100' and S100''; to each individual centrifugal weight FW500 the other side is connected to movable arm A500, which is connected to the fixing seats C300' and C300'' (or to the fixing seat of the body extension of the electric machinery rotor structure) installed with pivotal joint structure SC500, for the pulling of individual electric machinery rotors R100' and R100'', and to the two sets of individual electric machinery rotating shaft S100' and S100'' of the electric machinery rotor R100' and R100'', there is installed the individual pre-stressed springs SP100' and SP100'' which exhibit regression during deceleration, and according to the needs selectively to each individual electric machinery rotating shaft S100' and S100'' there are installed axial position limiting structure D100.

9. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, to which are installed two sets of electro-magnetic field F100' and F100'' and two sets of electric machinery rotor R100' and R100'', jointly coupled to the single common electric machinery rotating shaft S100''' structure, in between the two sets of electric machinery rotors R100' and R100'' there are installed single common centrifugal pulling mechanism FCD100''', to the single set of common centrifugal pulling mechanism FCD100''' there is installed centrifugal weight FW500, to the centrifugal weight FW500 there is installed a pivotal joint structure SC500 to which both sides are connected to movable arms A500, of which one of the side is connected to the movable arm A500, to which is connected

09363374-092704
F072509-4255550

to fixing seat (or the fixing seat which is the body extension
of electric machinery rotor structure) C300' of the pivotal
joint structure SC500 so as to be connected to electric
machinery rotor R100'; to which the other side is connected
5 to movable arm A500 for the connection to the fixing seat
(or the fixing seat which is the body extension of electric
machinery rotor structure) C300'' of the pivotal joint
structure SC500 so as to be connected to the electric machinery
rotor R100'', and further for the electric machinery rotors
10 R100' and R100'' through the actions of the single set common
centrifugal pulling mechanism FCD100''' and the pre-stressed
spring SP100''', the common driving electric machinery
rotors R100' and R100'' produce axial control displacement;
whereas between each individual electric machinery rotor
15 R100' and R100'' and their respective coupling electric
machinery rotating shaft S100''', there are installed
plum-flower shape axis or any other key way structures SL100
for the axial displacement, or further in between the groove
like linear interactive bodies there are installed ball
20 bearing or roller bearing structures.

10. As claimed in Claim 1 of the detailed description of the
preferred embodiments on the rotor axial activation
modulation of electric machinery due to centrifugal force,
further between the common electric machinery rotating shaft
25 S100''' and rotor R100' of the electric machinery, there
is reserved an installation of plum-flower shape axis or
any other key way structures SL100, or further in between
the groove-like linear interactive bodies there are
installed ball bearing or roller bearing structures, whereas
30 with electric machinery rotor R100'' the connection is direct,

so as to make use of the actions of single common centrifugal pulling mechanism FCD100''' and pre-stressed spring SP100''', to singularly drive the electric machinery rotor R100' to produce axially controlled displacement.

5 11. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, in between the two sets of independent electric machinery rotating shaft S100' and S100'' can further install two sets
10 of electro-magnetic fields F100' and F100'' and two sets of electric machinery rotors R100' and R100'', and between the electric machinery rotating shafts S100' and S100'' can selectively install controllable clutch CL100; whereas the
15 controllable clutch includes electrical, or magnetic, or mechanical, or human, or fluid, or any other operable means of power to control the transmission structure, including frictional or let-in type clutch or centrifugal clutch, etc., for rotary dynamics transmission or breaking function
clutches; by controlling two sets of electric machinery
20 rotors R100' and R100'' to drive the electric machinery rotating shafts S100' and S100'' between which to perform individual independent driving or connected common driving situation.

12. As claimed in Claim 1 of the detailed description of the
25 preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, to which are installed two sets of electro-magnetic field F100' and F100'' and two sets of electric machinery rotors R100' and R100'' and two sets of electric machinery rotating
30 shafts S100' and S100''; in between the two sets of electric

095335-092701

coupling electric machinery rotating shafts S100' and S100'',
there is installed plum-flower-shaped shaft or any other
similar shaft for axial displacement keyway structure SL100,
or further in between the groove-like linear interactive
5 bodies there are installed ball bearing or roller bearing
structures, with the help of centrifugal pulling mechanism
FCD100' and FCD100'' whose centrifugal force changes
depending on the rotor speed and with the help of axial
pre-stressed spring SP1000' and SP100'', individually
10 driving the electric machinery rotors R100' and R100'' to
produce axial modulating displacement.

13. As claimed in Claim 1 of the detailed description of the
preferred embodiments on the rotor axial activation
modulation of electric machinery due to centrifugal force,
15 to which are installed two sets of electro-magnetic fields
F100' and F100'' and two sets of electric machinery rotors
R100' and R100'', and constituted of a single common electric
machinery rotating shaft S100'', and by using the two sets
of centrifugal pulling mechanisms FCD100' and FCD100'' to
20 individually coupled in between the two electric machinery
rotors R100' and R100'' and motor shell H100, and for the
centrifugal pulling mechanism FCD100' and FCD100'' there
are installed individual centrifugal weight FW500, and to
the centrifugal weight FW500 there is installed the pivotal
25 joint structure SC500 for the connection of movable arm A500
on both sides, each centrifugal weight FW500 of which one
of the side is connected to the movable arm A500, to which
is connected to fixing seat (or the fixing seat which is
the body extension of electric machinery rotor structure)
30 C300' and C300'' of the pivotal joint structure SC500 so

as to be connected to electric machinery rotors R100' and R100'', the other side of each individual centrifugal weight FW500 is through the help of circular washer WS100' and WS100'' and through B200' and B200'' coupled to the fixing seat C200' and C200'' connected to the pivotal joint structure SC500 and connected to stator H100, and further to form a rotary coupling with motor coupling and with axially resisting force functions; whereas between each individual electric machinery rotors R100' and R100'' and their respective coupling electric machinery rotating shaft S100''', there are installed plum-flower shape shaft or any other key way structures SL100 for the axial displacement, or further in between the groove-like linear interactive bodies there are installed ball bearing or roller bearing structures, so as to make use of the centrifugal pulling mechanism FCD100' and FCD100'' and installed between the circular washer WS100' and WS100'' and the fixing seats C200' and C200'' are the axial pre-stressed springs SP100' and SP100'' which drives electric machinery rotors R100' and R100'' to produce axial modulating displacement.

14. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, between the common rotating shaft of the electric machinery S100''' and the electric machinery rotor R100', there is reserved an installation of plum-flower shape axis or any other key way structures SL100, or further in between the groove-like linear interactive bodies there are installed ball bearing or roller bearing structures, whereas with electric machinery rotor R100'' the connection is direct,

so as to make use of the actions of single common centrifugal pulling mechanism FCD100''' and pre-stressed spring SP100''', to singularly drive the electric machinery rotor R100' to produce axially modulated displacement.

5 15. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, in between the two sets of independent rotating shaft S100' and S100'' of the electric machinery can further be installed
10 two sets of electro-magnetic fields F100' and F100'' and two sets of electric machinery rotors R100' and R100'', and between the rotating shaft of the electric machinery S100' and S100'' can selectively install controllable clutch CL100; whereas the controllable clutch includes electrical, or
15 magnetic, or mechanical, or human, or fluid, or any other operable means of power to control the transmission structure, including frictional or let-in type clutch or centrifugal clutch, etc., for rotary dynamics transmission or breaking function clutches; so as to perform separate independent
20 driving or connecting common driving between the two sets of electric machinery rotors R100' and R100'' driving electric machinery rotating shaft S100' and S100''.

16. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation
25 modulation of electric machinery due to centrifugal force, to which are installed two sets of electro-magnetic fields F100' and F100'' and two sets of rotating shaft S100' and S100'' of the electric machinery, and there are installed two sets of electric machinery R100' and R100'' exhibiting
30 serial common structure as shown in the realization example

in Fig. 4, to which between its electric machinery rotating shaft S100' and S100'' there is installed a controllable clutch CL100; the controllable clutch CL100 includes electrical, or magnetic, or mechanical, or human, or fluid, or any other operable means of power to control the transmission structure, including frictional or let-in type clutch or centrifugal clutch, etc., for rotary dynamics transmission or breaking function clutches, so as to produce individual independent driving or connected common driving for the electric machinery rotating shafts S100' and S100'' which are driven by the two sets of electric machinery rotors R100' and R100''.

17. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, to which are installed two sets of electro-magnetic field F100' and F100'' and two sets of rotating shafts S100' and S100'' of the electric machinery, and with two sets of electric machinery as claimed in Claim 5 of the detailed description of the preferred embodiments exhibiting serial common structures, and between the two rotating shafts of the electric machinery of the two sets of electric machinery rotors R100' and R100'' there is installed controllable clutch CL100; the controllable clutch CL100 includes electrical, or magnetic, or mechanical, or human, or fluid, or any other operable means of power to control the transmission structure, including frictional or let-in type clutch or centrifugal clutch, etc., for rotary dynamics transmission or breaking function clutches, so as to perform individual independent driving or connected common driving

for the electric machinery rotating shafts S100' and S100'' which are driven by the two sets of electric machinery rotors R100' and R100''.

18. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, to which are installed two sets of electro-magnetic field F100' and F100'' and two sets of rotating shaft S100' and S100'' of the electric machinery, are two sets of rotating electric machinery as claimed in Claim 6 of the detailed description of the preferred embodiments exhibiting serial common structures, and between the two electric machinery rotating shafts of the two sets of the electric machinery rotors R100' and R100'' there is installed the controllable clutch CL100; the controllable clutch CL100 includes electrical, or magnetic, or mechanical, or human, or fluid, or any other operable means of power to control the transmission structure, including frictional or let-in type clutch or centrifugal clutch, etc., for rotary dynamics transmission or breaking function clutches, so as to perform individual independent driving or connected common driving for the rotating shafts S100' and S100'' of the electric machinery which are driven by the two sets of electric machinery rotors R100' and R100''.

19. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, can be the rotating electric machinery with a structure of two electric machinery rotors and individual or common electric machinery magnetic field, with the two electric

machinery rotors consist of two sets of same or mixture of different structures as claimed in Claims 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, or 18 of the detailed description of the preferred embodiments.

5 20. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, can be the rotating machine with a structure of two electric machinery rotors and individual or common electric machinery magnetic field, with one of the two electric machinery rotors
10 consist of one of the different structures as claimed in Claims 2, 3, 4, 5, or 6 of the detailed description of the preferred embodiments, and the other electric machinery rotor is consist of the common electric machinery rotor which
15 does not produce axial displacement or other structure which can produce axial activation displacement.

21. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force,
20 can be two common structure rotating electric machinery with dual electric machinery rotors and individual or common electric machinery magnetic field, including both are electric generators or both are electric motors, or one is a generator and the other is a motor.

25 22. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, of which the electric machinery magnetic effect structure of the electric machinery rotor R100 and electro-magnetic
30 field F100 includes: the axial stack height of the magnetic

core of the electric machinery rotor is greater than that of the electric machinery magnetic field.

23. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, of which the modulation method of the characteristics of the electric generator or electric motor that generates axial displacement between the electric machinery rotor and electro-magnetic field, including controllable voltage, current, frequency, etc. inputs versus output linear characteristics of the electric generator, and controllable motor speed, torque, synchronous or asynchronous, etc. input versus output linear characteristics of the electric motor.

24. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, when the axial stack height of the magnetic core of the electric machinery rotor is greater than that of the electric machinery magnetic field, the modulation method of the electric machinery function is to make use of the magnetic poles of the electric machinery rotor and the electric machinery magnetic field in the axial corresponding displacement generated by using the centrifugal force, so as to couple the electric magnetic machinery rotor with fixed characteristics with different magnetic flux density or different gap, or different magnetic or different exciting method or any other different structure of different electric machinery physical property or electric machinery magnetic field structure of different electric machinery characteristics, so as to generate the needed operation and

output characteristics of the generator or motor.

25. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, for commutator type electric machinery, if the axial thickness of the magnetic poles of the electric machinery rotor is smaller than the thickness of the magnetic poles of the magnetic field of the electric machinery, the armature ARM100 of the commutator can be used together with the special axial extended commutator CM100 installed specially for axial activation control, so as to increase the coupling range with electric brush BU100, for the matching of different structure type or different electric machinery magnetic field F100''' of the different electric machinery characteristics, during the axial pulling displacement by using centrifugal pulling mechanism FCD100, in producing corresponding different electric machinery characteristics; as shown in Fig. 18 is the realization example of this invention in the axial extension commutator armature.
26. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, when the axial stack height of the magnetic core of the electric machinery rotor is greater than that of the electro-magnetic field, the modulation method of the electric machinery function is to make use of the electric machinery rotor and electro-magnetic field to generate axial pulling displacement by using the centrifugal pulling mechanism FCD100, and the electric machinery rotor coupled by the electric machinery magnetic field in turn makes use

of the electric machinery rotor R100''' with axial multiple circuit squirrel-cage rotor structure presenting different electric machinery characteristics, and each squirrel-cage rotor structure can choose parameters including number of squirrel-cage conductors, cross sectional area, conductivity, depth of inset, shape of cross section, and the gap of electric machinery magnetic field, so as to generate axial displacement with corresponding different electric machinery characteristics in the electric machinery magnetic field and the electric machinery rotors.

27. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, the squirrel-cage rotor structure can consist of rotors excited by windings or permanent magnetic type or salient type or hysteresis type or eddy current type, and by selecting the size of outer diameter and inner diameter of the electric machinery magnetic field and electric machinery rotors, and in the axial pulling by the centrifugal pulling mechanism structure FCD100 pulling electric machinery rotor, causing the axial variations in the gap between the electric machinery magnetic field and electric machinery rotor.

28. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, the various similar or different alternating current or direct current and brush or brushless rotating electric machinery magnetic field and electric machinery rotor structure, and by selecting different axial position and size of electric machinery magnetic field and electric

machinery rotor, there can be similar or different inner diameter or outer diameter, or electric machinery magnetic field or electric machinery rotor made of same or different number of poles, and same or different method of excitation, or constitute of electric machinery rotor of same or different electric machinery characteristics or structures, the desired operation and characteristics of generator or motor can be selected.

29. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, The electric machinery rotor can be formed in one body, and during the operating state with the electric machinery in the different axial corresponding position, the working section for different axial coupling position with the electric machinery magnetic field, can be with same electric machinery characteristics or different electric machinery characteristics; and electric machinery rotor can be formed in one body or at least two electric machinery rotor structures $R_{100} \sim R_{100+n}$ consist of a few sectors of different electric machinery characteristics exhibiting axial overlapping.

30. As claimed in Claim 1 of the detailed description of the preferred embodiments on the rotor axial activation modulation of electric machinery due to centrifugal force, the electric machinery magnetic field can be formed in one body, and during the working section of different axial coupling position with the electric machinery rotor, can be with same electric machinery characteristics or different electric machinery characteristics; and electric machinery magnetic field can be formed in one body or at least two

electric machinery magnetic field structures R100~R100+n
consist of a few sectors of different electric machinery
characteristics presenting axial overlapping.

31. As claimed in Claim 1 of the detailed description of the
preferred embodiments on the rotor axial activation
modulation of electric machinery due to centrifugal force,
its electric machinery rotor and electric machinery magnetic
field, of which the mechanical corresponding driving
relationship of both include: External electric machinery
rotor rotary electric machinery structure; Internal electric
machinery rotor rotary electric machinery structure; Dual
moving type in which the magnetic field structure and electric
machinery rotor both are rotary.

32. As claimed in Claim 1 of the detailed description of the
preferred embodiments on the rotor axial activation
modulation of electric machinery due to centrifugal force,
its structure includes: Cylindrical rotating electric
machinery structure; Cone rotating electric machinery
structure.

20